



[Close This Document](#)

ALTUGLAS INTERNATIONAL SHEET PRODUCTS: ANSI Z97.1 - SAFETY GLAZING

- Plexiglas[®] MC and G sheet clear and all colors can meet the requirements of ANSI Z97.1 at nominal 0.080" and greater thicknesses.
- Tuffak[®] A and CM-2 sheet clear and colors sheets can meet the requirements of ANSI Z97.1 at nominal .093" and greater.

Consumer Product Safety Commission (CPSC)

- Plexiglas sheet is also acceptable for use in Category I or Category II safety glazing applications as defined by the Consumer Product Safety Commission in 16 CFR Part 1201.

The statements, technical information and recommendations obtained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OR MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein should be construed as an inducement to infringe any patent, and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

See MSDS for Health and Safety Considerations.

© 2006 Arkema