



# GHS SAFETY DATA SHEET

## SCIGRIP® 3 Solvent Cement for Bonding Acrylics

Date Revised: JUN 2012  
Supersedes: MAY 2012

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** SCIGRIP® 3 Solvent Cement for Acrylic  
**PRODUCT USE:** Solvent Cement for Bonding Acrylics  
**SUPPLIER:**

**MANUFACTURER:** SCIGRIP Smarter Adhesive Solutions  
600 Ellis Road, Durham, NC 27703 - USA  
P.O. Box 12729, Research Triangle Park, NC 27709 - USA  
Tel. 1-919-598-2400

**EMERGENCY:** Transportation: CHEMTEL Tel. 800.255-3924, 813-248-0585 (International)

**Medical:** Tel. 800.451.8346, 760.602.8703 3E Company (International)

### SECTION 2 - HAZARDS IDENTIFICATION

#### GHS CLASSIFICATION:

Health	Environmental	Physical
Acute Toxicity: Category 4 Skin Irritation: Category 2 Skin Sensitization: NO Eye: Category 2	Acute Toxicity: None Known Chronic Toxicity: Category 3	None Known

#### GHS LABEL:



**Signal Word:**  
Danger

**WHMIS CLASSIFICATION:** CLASS D, DIVISION 1B  
CLASS D, DIVISION 2A & 2B

Hazard Statements		Precautionary Statements
H315: Causes skin irritation H336: May cause drowsiness or dizziness H350: May cause cancer H412: Harmful to aquatic life with long lasting effects	H319: Causes serious eye irritation H341: Suspected of causing genetic defects H351: Suspected of causing cancer	P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking P261: Avoid breathing dust/fume/gas/mist/vapors/spray P280: Wear protective gloves/protective clothing/eye protection/face protection P337+P313: Get medical advice/attention P403+P233: Store in a well ventilated place. Keep container tightly closed P501: Dispose of contents/container in accordance with local regulation

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS #	REACH	CONCENTRATION
			Pre-registration Number	% by Weight
Methylene Chloride * # (dichloromethane)	75-09-2	200-838-9	17-2119926076-39-0000	75 - 90
Trichloroethylene * #	79-01-6	201-167-4	N/A	5 - 15
Methyl Methacrylate Monomer *, Stabilized (MMA)	80-62-6	201-297-1	05-2116297731-37-0000	1 - 2

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.  
\* Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).  
# indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

### SECTION 4 - FIRST AID MEASURES

**Contact with eyes:** Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.  
**Skin contact:** Wash skin with soap and water. If irritation develops, get medical attention  
**Inhalation:** Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.  
**Ingestion:** Do not induce vomiting. Seek medical advice immediately.

### SECTION 5 - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Water fog or fine spray, carbon dioxide, dry chemical or foam.  
**Unsuitable Extinguishing Media:** Dry chemical powder.  
**Exposure Hazards:** Inhalation and dermal contact.  
**Combustion Products:** Hydrogen chloride, trace amounts of chlorine, phosgene.  
**Protection for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing.

	HMIS	NFPA	
Health	2	2	0-Minimal
Flammability	0	0	1-Slight
Reactivity	0	0	2-Moderate
			3-Serious
			4-Severe

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Clear all personnel from area. Do not breathe vapors. Ventilate area of leak or spill. Wear protective equipment positive pressure self contained or air supplied breathing apparatus. Follow confined space entry procedures.  
**Environmental Precautions:** Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.  
**Methods for Cleaning up:** Mop or soak up immediately. Place in properly labeled metal containers.  
**Materials not to be used for clean up:** Zinc, Aluminum or plastic containers

### SECTION 7 - HANDLING AND STORAGE

**Handling:** Avoid breathing of vapor, avoid contact with eyes, skin and clothing. Do not swallow. Use with adequate ventilation. Do not cut, drill, grind, weld or perform similar operations on or near empty containers. Vapors of this product are heavier than air and will collect in low areas. Do not eat, drink or smoke while handling.  
**Storage:** Store in a dry place. Keep container tightly closed when not in use. Store below 80°F (27°C). Follow all precautionary information on container label, product bulletins and solvent bonding literature.

### SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH TLV	ACGIH STEL	OSHA PEL	OSHA STEL:
	Methylene Chloride (dichloromethane)	50 ppm	N/E	25 ppm	125
	Trichloroethylene	50 ppm	100 ppm	100 ppm	N/E
	Methyl Methacrylate Monomer, Stabilized (MMA)	50 ppm	100 ppm	100 ppm	N/E

**Engineering Controls:** Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Lethal concentrations may exist in areas with poor ventilation

**Monitoring:** Maintain breathing zone airborne concentrations below exposure limits.

#### Personal Protective Equipment (PPE):

**Eye Protection:** Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.  
**Skin Protection:** Prevent contact with the skin as much as possible. Use protective clothing chemically resistant to this material. Remove contaminated clothing immediately, wash skin area with soap and water and launder clothing before reuse or dispose of properly.

**Respiratory Protection:** Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.



# GHS SAFETY DATA SHEET

## SCIGRIP® 3 Solvent Cement for Bonding Acrylics

Date Revised: JUN 2012  
Supersedes: MAY 2012

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Clear, thin liquid	<b>Odor Threshold:</b>	250 ppm (Methylene Chloride)
<b>Odor:</b>	Irritating	<b>Evaporation Rate:</b>	> 1.0 (BUAC = 1)
<b>pH:</b>	Not Applicable	<b>Flammability:</b>	None
<b>Melting/Freezing Point:</b>	-96.7°C (-142.1°F) (Methylene Chloride)	<b>Flammability Limits:</b>	<b>LEL:</b> 14% (Methylene Chloride) <b>UEL:</b> 22% (Methylene Chloride)
<b>Boiling Point:</b>	39.8°C (104°F) Based on first boiling component: Methylene Chloride	<b>Vapor Pressure:</b>	355 mmHG @ 20C (Methylene Chloride)
<b>Flash Point:</b>	None (Methylene Chloride)	<b>Vapor Density:</b>	>2.0 (Air = 1)
<b>Specific Gravity:</b>	1.32 @23°C ( 73.4°F)		
<b>Solubility:</b>	1.3% @ 25°C(Methylene Chloride)		
<b>Partition Coefficient n-octanol/water:</b>	Not Available		
<b>Auto-ignition Temperature:</b>	556°C (1033°F) (Methylene Chloride)		
<b>Decomposition Temperature:</b>	Not Applicable		
<b>VOC Content:</b>	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤250 g/l.		

### SECTION 10 - STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under recommended storage conditions. (See Section 7)
<b>Hazardous decomposition products:</b>	Depending on temperature and air supply, may include hydrogen chloride, trace amounts of chlorine, phosgene.
<b>Conditions to avoid:</b>	Avoid open flames, welding arcs, or other high temperature sources. Avoid direct sunlight.
<b>Incompatible Materials:</b>	Oxidizers, strong bases, amines, metals such as zinc powders, aluminum or magnesium powders, potassium sodium.

### SECTION 11 - TOXICOLOGICAL INFORMATION

**Likely Routes of Exposure:** Inhalation, Eye and Skin Contact

#### Acute symptoms and effects:

<b>Inhalation:</b>	Excessive overexposure may cause irritation to nose and throat. In confined areas, vapor can accumulate and can cause unconsciousness.
<b>Eye Contact:</b>	May cause moderate eye irritation which may be slow to heal. May cause slight corneal injury. Vapor may cause mild discomfort and redness.
<b>Skin Contact:</b>	Prolonged contact may cause skin burns. May cause more severe response on covered skin (under clothing and gloves).
<b>Ingestion:</b>	Low toxicity if small amount swallowed, however larger amounts may cause injury. Aspiration into the lungs may occur during ingestion or vomiting.

**Chronic (long-term) effects:** IARC Classification 2B (Methylene Chloride)

Toxicity:	LD50	LC50	Target Organs
Methylene Chloride (dichloromethane)	Oral: 1500- 2500 mg/kg (rat) , Dermal: Not Determined	Inhalation 7 hrs. >10000 PPM (rat)	STOT SE3
Trichloroethylene	Oral: 5650 mg/kg (rat)	Inhalation 4 hrs. 12000 PPM (rat)	STOT SE3
Methyl Methacrylate Monomer, Stabilized (MMA)	Oral: 7900 mg/kg (rat), Dermal: >35000 mg/kg (rabbit)	Inhalation: 3 hrs. 7093 PPM (rat)	STOT SE3

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Category 2	Not Established	Not Established	Not Established

### SECTION 12 - ECOLOGICAL INFORMATION

<b>Ecotoxicity:</b>	None Known
<b>Mobility:</b>	In normal use, emission of volatile organic compounds (VOC's) to the air takes place, typically at a rate of ≤250 g/l. Mobility in soil is high.
<b>Degradability:</b>	Not readily biodegradable
<b>Bioaccumulation:</b>	Low

### SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert.

### SECTION 14 - TRANSPORT INFORMATION

<b>Proper Shipping Name:</b>	Dichloromethane (Mixture)
<b>Hazard Class:</b>	6.1
<b>Secondary Risk:</b>	None
<b>Identification Number:</b>	UN 1593
<b>Packing Group:</b>	PG III
<b>Label Required:</b>	Toxic (Domestic USA and International)
<b>Marine Pollutant:</b>	NO

#### EXCEPTION for Ground Shipping

**DOT Limited Quantity:** Up to 4L per inner packaging, 30 kg gross weight per package.  
**Consumer Commodity:** Depending on packaging, these quantities may qualify under DOT as "ORM-D".

#### TDG INFORMATION

<b>TDG CLASS:</b>	Toxic 6.1
<b>SHIPPING NAME:</b>	Dichloromethane (Mixture)
<b>UN NUMBER/PACKING GROUP:</b>	UN 1593, PG III

### SECTION 15 - REGULATORY INFORMATION

<b>Precautionary Label Information:</b>	Toxic, Suspected Carcinogen	Ingredient Listings:	USA TSCA, Europe EINECS, Canada DSL, Australia, AICS, Korea ECL/TCCL, Japan MITI (ENCS), <b>CA Prop 65</b>
<b>Symbols:</b>	Toxic		
<b>Risk Phrases:</b>	R36/38: Irritating to eyes and skin. R40: Limited evidence of a carcinogenic effect R45: May cause cancer.	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67: Vapors may cause drowsiness and dizziness R68: Possible risk of irreversible effects	
<b>Safety Phrases:</b>	S2: Keep out of the reach of children. S23: Do not breathe gas/fumes/vapour S24/25: Avoid contact with skin and eyes. S36/37: Wear suitable protective clothing and gloves.	S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S53: Avoid exposure - obtain special instructions before use. S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.	

### SECTION 16 - OTHER INFORMATION

<b>Specification Information:</b>		
<b>Department issuing data sheet:</b>	IPS, Safety Health & Environmental Affairs	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
<b>E-mail address:</b>	<EHSinfo@ipscorp.com>	
<b>Training necessary:</b>	Yes, training in practices and procedures contained in product literature.	
<b>Reissue date / reason for reissue:</b>	06/06/2012 / Updated GHS Standard Format	
<b>Intended Use of Product:</b>	Solvent Cement for Bonding Acrylics	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.